

EQUIPMENT

CONTENTS

DIAGNOSIS SYSTEM	2	LAMPS	2
Diagnosis Connector	2	Exterior Lamps	2
		HEATER AND AIR CONDITIONER	2





DIAGNOSIS SYSTEM


In light of the AYC system's incorporation, AYC system inspection terminals have been added to the diagnosis connector to facilitate maintenance.

Diagnosis function		AYC
Diagnosis code output		○
Service data output		○
Actuator test		○
Substitutional means for reading diagnosis codes	Flashing of warning lamp	○
	Deflection of needle on analog voltmeter	—
Diagnosis code retention	Until battery disconnection	○
	EEPROM*	—
Deletion of diagnosis codes using MUT-II		○

*: Memory contents are retained unless deleted electrically.

DIAGNOSIS CONNECTOR

Terminal No.	Signals
7	AYC (added), MPI, ELC-4A/T, 4ABS



LAMPS

EXTERIOR LAMPS

FOG LAMPS

The fog lamps are a reflector type made by PIAA <standard on GSR; optional on RS>.

Specifications

Item	Specification
Fog lamp (PIAA)	55W

HEATER AND AIR CONDITIONER

The RS is equipped with only a manual heater. The GSR is equipped with a fully automatic air conditioner as standard. Each system is basically the same as that used in the previous model.